

CONCEALED SLIDE ARM DOOR CLOSERS

# ITS.11204.3.5

Renowned for its slimline mechanism (32mm body) and suitability for assisting BS8300 requirements, the key difference between the ITS.11204 and the ITS.11204.3.5 is the slimline micro rail that comes as standard on the ITS.11204.3.5, allowing the concealed closer to be used in door frames of thinner and more shallow widths.

- Slim micro rail of 20 x 30mm
- Power Adjustable by spring, size 2-4
- Available in Silver & Satin Nickel for next day delivery
- Designed for hollow profile frames, but can be used in solid timber frames




Opening Angle  
110°



Two-Stage  
Speed Regulation



Guarantee



Max Door  
Width



Max Door  
Weight



Intumescent  
kit (IP.114M)

Product Features	ITS.11204.3.5
Delayed Action	-
Back Check	-
Opening Angle	110°
Door Width	595-1100mm
BS8300 Min Door Width	835mm
Max Door Weight	<130kg
Power Adjustment	By Spring
Hold Open (not for fire doors)	o
Dimensions	W243 x H52 x D32mm
<b>Certification Compliance</b>	
EPD 3.09E+01 kg CO <sub>2</sub> eq	✓
<b>Key:</b> ✓ Yes   - No   o Option	

Finishes

See page 98 for more detail



SE  
Silver



SNP  
Satin Nickel

