DECLARATION OF PERFORMANCE



DoP-ITS.11204.3.5-UKCA

(ITS.11204.3.5)



- Unique identification code of the product / type: ITS.11204 2-4 variable power Concealed Door Closer with micro-rail, adjustable latch action, 110 degree maximum opening angle.
- Re-order Code allowing identification of the construction product as required under Article 11(4) of CPR: 11420, 11421, 11418, 11419
- Intended use:- For use on fire/smoke compartmentation doors, when fitted in accordance with the supplied fitting instructions and maintained to the manufacturers O&M Manual.
- Manufacturer:- Rutland UK, Unit 4, Holmewood Business Park, Chesterfield Road, Chesterfield, S42 5US
- System or systems assessment and verification of constancy of performance (AVCP):- System 1
- Harmonised Standard:- EN 1154:1996 + A1:2002 + AC:2006
- Notified Body:- Warrington Certification
- Certification No.:- 1121-CPR-UK-AD8096
- Declared Performance:-

Conditioning: Parallel Arm Fixing (Fig 61) power size 2-4, with adjustable latch action and optional back check, 110 degree maximum opening angle

Essential Characteristics	Performance	Harmonised Technical Specification
Self-closing (5.2.1 General)		
5.2.2 Durability	500,000 test cycles	
5.2.3 Closing moment	Power size 2 - 4	
5.2.4 Opening moment	Power size 2 - 4	
5.2.5 Efficiency	Pass	
5.2.6 Closing time	Pass	
5.2.7 Angles of operation	Grade 3 for closing doors from 120 degrees	EN 1154:1996 +
5.2.8 Overload performance	Pass	A1:2002 + AC:2006
5.2.9 Temperature dependence	-15°C to +40°C	
5.2.10 Fluid leakage	Pass	
5.2.11 Damage	Pass	
5.2.12 Latch control	Pass	
5.2.13 Back check	Pass	
5.2.15 Adjustable closing force	Pass	

DECLARATION OF PERFORMANCE



Durability of Self Closing		
5.2.2 Durability	500,000 test cycles – Grade 8	EN 1154:1996 + A1:2002 + AC:2006
5.2.17 Corrosion resistance	High corrosion resistance - Grade 3 (96 hours)	
Dangerous Substances	Pass: the materials in the door closer do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kevin O'Reilly Technical Director

Dated 18-04-2024