

DECLARATION OF PERFORMANCE



DoP Number: TS.9205-1-CE

(TS.9205 Fig 1)

- Unique identification code of the product / type:-
TS.9205 DA BC 2-5 variable power Surface Fixed Door Closer with Fig 1 Standard Fixing Position, with optional back check, delayed action and adjustable latch action, 180 degree maximum opening angle.
- **Re-order Code allowing identification of the construction product as required under Article 11(4) of CPR:**
11598, 11626, 11629, 11617, 11622, 11632, 11620, 11884, 11883, 11664, 11692, 11695, 11683, 11688, 11698, 11686, 11773, 11912, 11730, 11758, 11761, 11749, 11754, 11764, 11752, 11748, 12136, 11760, 12129, 12131, 12130, 12137, 11917, 12095, 11916, 12151, 11733, 11667, 11601
- Intended use:- On fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors)
- Manufacturer:- Rutland Door Controls Europe Limited, Unit 5B, Fingal Bay Business Park, Balbriggan, Dublin, Ireland
- System or systems assessment and verification of constancy of performance (AVCP):- System 1
- Harmonised Standard:- EN 1154:1996 + A1:2002 / AC:2006
- Notified Body:- Efectis EU notified body no. 1812
- Certification of Conformity No.:- 1812-CPR-1809 dated 08-01-2024
- Declared Performance:-

Conditioning: Standard Position (Fig 1) power size 2-5, with optional back check, delayed action and adjustable latch action, 180 degree maximum opening angle

Essential Characteristics	Performance	Harmonised Technical Specification
<i>Self-closing (5.2.1 General)</i>		EN 1154:1996 + A1:2002 / AC:2006
5.2.2 Durability	500,000 test cycles	
5.2.3 Closing moment	Power size 2 - 5	
5.2.4 Opening moment	Power size 2 - 5	
5.2.5 Efficiency	Pass	
5.2.6 Closing time	Pass	
5.2.7 Angles of operation	Grade 4 for closing doors from 180 degrees	
5.2.8 Overload performance	Pass	
5.2.9 Temperature dependence	-15°C to +40°C	
5.2.10 Fluid leakage	Pass	
5.2.11 Damage	Pass	
5.2.12 Latch control	Pass	
5.2.13 Back check	Pass	
5.2.14 Delayed Closing	Pass	

DECLARATION OF PERFORMANCE



5.2.15 Adjustable closing force	Pass
5.2.16 Zero position	NPD
5.2.18 Suitable for Fire/ Smoke	Grade 1

<i>Durability of Self Closing</i>		EN 1154:1996 + A1:2002 / AC:2006
5.2.2 Durability	500,000 test cycles – Grade 8	
5.2.17.1 Corrosion resistance	High corrosion resistance - Grade 3 (96 hours)	
5.2.17.2 Corrosion resistance	Pass	
Dangerous Substances	Pass: the materials in the door closer do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

The performance of the product identified above is in conformity with the set of declared performance/s.

This Declaration of Performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kevin O'Reilly - Technical Director
 At Rutland Door Controls Europe Limited
 Unit 5B, Fingal Bay Business Park, Balbriggan, Dublin, Ireland

on 10-03-2025

DECLARATION OF PERFORMANCE



DoP-TS.9205-66-120-CE

(TS.9205 Fig 66 Parallel Arm Push Side - 120°)

- Unique identification code of the product / type:-
TS.9205 DA BC 2-4 variable power Surface Fixed Door Closer with Fig 66 Parallel Arm Fixing Position using small bracket PAB 2, with optional back check, delayed action and adjustable latch action, 120 degree maximum opening angle.
- **Re-order Code allowing identification of the construction product as required under Article 11(4) of CPR:**
11598, 11626, 11629, 11617, 11622, 11632, 11620, 11884, 11883, 11664, 11692, 11695, 11683, 11688, 11698, 11686, 11773, 11912, 11730, 11758, 11761, 11749, 11754, 11764, 11752, 11748, 12136, 11760, 12129, 12131, 12130, 12137, 11917, 12095, 11916, 12151, 11733, 11667, 11601
- Intended use:- On fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors)
- Manufacturer:- Rutland Door Controls Europe Limited, Unit 5B, Fingal Bay Business Park, Balbriggan, Dublin, Ireland
- System/s assessment and verification of constancy of performance (AVCP):- System 1
- Harmonised Standard:- EN 1154:1996 + A1:2002 / AC:2006
- Notified Body:- Efectis EU notified body no. 1812
- Certification of Conformity No.:- 1812-CPR-1809 dated 08-01-2024
- Declared Performance:-

Conditioning: Parallel Arm Fixing Position (Fig 66) power size 2-4, with optional back check, delayed action and adjustable latch action, 120 degree maximum opening angle

Essential Characteristics	Performance	Harmonised Technical Specification
<i>Self-closing (5.2.1 General)</i>		EN 1154:1996 + A1:2002 / AC:2006
5.2.2 Durability	500,000 test cycles	
5.2.3 Closing moment	Power size 2 - 4	
5.2.4 Opening moment	Power size 2 - 4	
5.2.5 Efficiency	Pass	
5.2.6 Closing time	Pass	
5.2.7 Angles of operation	Grade 3 for closing doors from 105 degrees	
5.2.8 Overload performance	Pass	
5.2.9 Temperature dependence	-15°C to +40°C	
5.2.10 Fluid leakage	Pass	
5.2.11 Damage	Pass	
5.2.12 Latch control	Pass	
5.2.13 Back check	Pass	
5.2.14 Delayed Closing	Pass	
5.2.15 Adjustable closing force	Pass	
5.2.16 Zero position	NPD	
5.2.18 Suitable for Fire/ Smoke	Grade 1	

DECLARATION OF PERFORMANCE



<i>Durability of Self Closing</i>		EN 1154:1996 + A1:2002 / AC:2006
5.2.2 Durability	500,000 test cycles – Grade 8	
5.2.17.1 Corrosion resistance	High corrosion resistance - Grade 3 (96 hours)	
5.2.17.2 Corrosion resistance	Pass	
Dangerous Substances	Pass: the materials in the door closer do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

The performance of the product identified above is in conformity with the set of declared performance/s.

This Declaration of Performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kevin O'Reilly - Technical Director
At Rutland Door Controls Europe Limited
Unit 5B, Fingal Bay Business Park, Balbriggan, Dublin, Ireland

on 10-03-2025

DECLARATION OF PERFORMANCE



DoP Number: TS.9205-66-180-CE

(TS.9205 Fig 66 Parallel Arm Push Side - 180°)

- Unique identification code of the product / type:-
- **TS.9205 DA BC 2-4 variable power Surface Fixed Door Closer with Fig 66 Parallel Arm Fixing Position using large bracket PAB 1, with optional back check, delayed action and adjustable latch action, 180 degree maximum opening angle.**
- **Re-order Code allowing identification of the construction product as required under Article 11(4) of CPR:**
11598, 11626, 11629, 11617, 11622, 11632, 11620, 11884, 11883, 11664, 11692, 11695, 11683, 11688, 11698, 11686, 11773, 11912, 11730, 11758, 11761, 11749, 11754, 11764, 11752, 11748, 12136, 11760, 12129, 12131, 12130, 12137, 11917, 12095, 11916, 12151, 11733, 11667, 11601
Intended use:- On fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors)
- Manufacturer:- Rutland Door Controls Europe Limited, Unit 5B, Fingal Bay Business Park, Balbriggan, Dublin, Ireland
- System/s assessment and verification of constancy of performance (AVCP):- System 1
- Harmonised Standard:- EN 1154:1997 + A1:2002 / AC:2006
- Notified Body:- Efectis EU notified body no. 1812
- Certification No.:- 1812-CPR-1809
- Declared Performance:-

Conditioning: Parallel Arm Fixing Position (Fig 66) power size 2-4, with optional back check, delayed action and adjustable latch action, 180 degree maximum opening angle

Essential Characteristics	Performance	Harmonised Technical Specification
<i>Self-closing (5.2.1 General)</i>		EN 1154:1996 + A1:2002 / AC:2006
5.2.2 Durability	500,000 test cycles	
5.2.3 Closing moment	Power size 2 - 4	
5.2.4 Opening moment	Power size 2 - 4	
5.2.5 Efficiency	Pass	
5.2.6 Closing time	Pass	
5.2.7 Angles of operation	Grade 4 for closing doors from 180 degrees	
5.2.8 Overload performance	Pass	
5.2.9 Temperature dependence	-15°C to +40°C	
5.2.10 Fluid leakage	Pass	
5.2.11 Damage	Pass	
5.2.12 Latch control	Pass	
5.2.13 Back check	Pass	
5.2.14 Delayed Closing	Pass	

DECLARATION OF PERFORMANCE



5.2.15 Adjustable closing force	Pass
5.2.16 Zero position	NPD
5.2.18 Suitable for Fire/ Smoke	Grade 1

<i>Durability of Self Closing</i>		EN 1154:1996 + A1:2002 / AC:2006
5.2.2 Durability	500,000 test cycles – Grade 8	
5.2.17.1 Corrosion resistance	High corrosion resistance - Grade 3 (96 hours)	
5.2.17.2 Corrosion resistance	Pass	
Dangerous Substances	Pass: the materials in the door closer do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

The performance of the product identified above is in conformity with the set of declared performance/s.

This Declaration of Performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kevin O'Reilly - Technical Director
 At Rutland Door Controls Europe Limited
 Unit 5B, Fingal Bay Business Park, Balbriggan, Dublin, Ireland

on 10-03-2025